



Technical data sheet

General data	
Frame size	100
Housing material	Aluminum
Install model	According to the standard
Type of feet	Removable feet
Net weight	22.1 kg
Insulation class	F
Protection degree	IP 55
Thermal protection	Bimetallic sensor
Rotation direction	Clockwise
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M20 × 1.5
Cooling	IC 411
Painting color	RAL 5010
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034



Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	1.5	kW
Frequency	50	Hz
Voltage (±5%)	230 400 276 480	V Δ @ 50Hz V Y @ 50Hz V Δ @ 60Hz V Y @ 60Hz
Rotation speed	955 1145	RPM @ 50Hz RPM @ 60Hz
Rated current	6.49 3.75	A (In) @ Δ 50Hz A (In) @ Y 50Hz
Starting current	5.5	×In
Rated torque	15.00	Nm (Mn)
Starting torque	2.4	×Mn
Breakdown torque	2.9	×Mn
Efficiency	82.5 83 81.8	IE3 @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.7	@ 100% load



Mechanical data		
Bearings brand	C&U	
Bearings type	6206 2RZ C3 6206 2RZ C3	(DE) (NDE)
Lifetime of bearings	20000 hours	
Allowed radial load Allowed axial load	1320.23 N 1093.1 N	
Moment of inertia	0.009137291	Kg*m ²
Noise level	61	dB(A)



T3A 100L-6 B3



T3A 100L-6 B5



T3A 100L-6 B14